



DATA SHEET

INNER HULL ADHESIVE REPOSITIONABLE GLUING SIMPLE FACE

Repositionable adhesive lining is a permanent adhesive aqueous dispersion based on acrylic copolymers.
Repositionable adhesive lining is used for gluing a variety of materials lining, textile, plastics, foams, felts.

PHYSICAL CHARACTERISTICS

Product base: Acrylic dispersion
Colour : Milky white when wet, the dry film is transparent
Dry extract (NFT 76101): About 69%
Density (NFT 70090): 1.1-1.2
pH (NFT 76093): About 5
Viscosity: About 32000 mPas
Flash point: -
Film strength: Resists moisture

APPLICATION

Gluing simple face.

Do not use for gluing of old ceiling.

Apply a layer of 80 to 200 g/m² (wet) with a brush. It's necessary that the glue becomes translucent (2 hours minimum at 20°C) before making placement. Assembly after drying with pressure during 20-30 s.

Use temperature: Above 18°C

Dilution: with water

Cleaning tools: With water (wet glue)

PACKING AND STORAGE

Packaging : 750 ml and 5 kg

Storage: 6 months in our original hermetically closed containers.
Fears freezing, coagulates

PRECAUTIONS FOR USE

Avoid contact with eyes and skin. No smoking, eating and drinking while using

HEALTH AND SAFETY

See data sheet

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.
Our company may modify all these details at any time*