



DATA SHEET

A COLD GALVANISING PRODUCT SOROGALVA

SOROGALVA is a product for cold galvanising or re-galvanising of all metal surfaces.

It can be applied directly to rusted surfaces, but nevertheless is not greasy or wet.

It can be used for repairs on ironwork, pipes, etc., and by virtue of its zinc content, is also used for the protection of anchors, chains, props, etc.

PHYSICAL CHARACTERISTICS

Product: Metal zinc
Appearance: Grey liquid
Density: 0.82
Solubility: Soluble in the usual solvents
Working temperature: 300°C
Flash point: -16°C
Self-igniting temperature: Between 365 and 470°C (butane)

APPLICATION

Shake the aerosol well before use.

Apply the spray at 20 - 30 cm from the dry, grease-free surface to be treated. In a saline environment, apply 2 coats of **SOROGALVA**.

Purge the aerosol well after use, with the spray head downward.

PACKING AND STORAGE

Packaging : Aerosol of 200 ml
Storage: Store in a well-ventilated place, away from sources of heat, frost, damp and sources of ignition.

PRECAUTIONS FOR USE

Container under pressure. Must be protected from direct sunlight. Do not expose to temperature over 50°C. Do not puncture the can, or burn it after use. Keep away from all sources of ignition. Do not smoke. Keep out of reach of children. Use only in a well ventilated area. Ventilate well after use. Do not breathe vapour.

HEALTH AND SAFETY

See data sheet

This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.

Our company may modify all these details at any time