



# DATA SHEET

## TWO-COMPONENT ADHESIVE – HIGH STRENGTH EPOXY GLUE TOPFIX

The two components epoxy glue, high reactivity serves to bond almost all materials: metals, ceramic, stone, wood, many hard plastics, ...

The glue hardens in 10 minutes at 20°C and is waterproof. It's resistance to chemical attack.

---

### PHYSICAL CHARACTERISTICS

	<i>Resin</i>	<i>Hardener</i>
Appearance	Light yellow	Light yellow to yellow brown
Flash point	> 150°C	> 100°C

---

### PREPARATION OF SURFACE

The surfaces must be absolutely clean and free of all traces of corrosion, calamine, oily bodies and silicones

---

### APPLICATION

Cut two holes the same diameter.

Carry on pressure on the end of the piston. Ratio 1/1 is automatically. Mix the two parts until smooth. it is usable for 3-4 minutes.

Apply glue to the surface to be joined, press it a few moments.

The glue is completely dry after 3 hours. It gets this final performance after 48 hours.

After use, wipe 2 ends of the syringe and block the plug located in the piston. This system cures even at temperature about 5°C, but in this case, we must consider the curing times longer (about 2 hours) at room temperature.

The influence of heat accelerates the curing process.

---

### PACKING AND STORAGE

Packaging : .....25 ml syringe

Storage:.....Store away from light in a dry, cool and well ventilated

---

### PRECAUTIONS FOR USE

Wear gloves and goggles.

---

### HEALTH AND SAFETY

See data sheet

---

This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.  
Our company may modify all these details at any time