



# DATA SHEET

## PROTECTIVE OIL FOR TEAK DECKS OF PLEASURE BOATS OILTECK

**OILTECK** provide excellent protection for teak against the effects of sun, salt and all similar damage suffered by decks on pleasure boats.

---

### PHYSICAL CHARACTERISTICS

Appearance : ..... Liquid fluid  
Colour : ..... Coppery  
Density at 20°C : ..... 0.82  
Flash point : ..... 43°C  
Solubility : ..... < 20 ppm in water, soluble in a lot of solvents usuals  
Cover : ..... 12 m<sup>2</sup>/l  
Drying : ..... Dry in 6 hours

---

### APPLICATION

**Joints on bridge: Make a test of compatibility.**

If the wood is dirty or grey, treat first of all with **NETATECK**. Shake the bottle well. Apply with the **OILTECK** brush in the direction of the fibres of the wood on a very dry surface.

Apply a second layer after leaving to dry for 8 hours.

Apply another coat on the first sign of ageing.

---

### PACKING AND STORAGE

Packaging : ..... 500 ml, 1 L and 5 L  
Storage: ..... Store in a well ventilated area. Keep away from sources of ignition, heat and direct sunlight

---

### PRECAUTIONS FOR USE

Wear gloves, goggles and mask. Do not smoke and eat when using the product.

---

### HEALTH AND SAFETY

See data sheet

---

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.  
Our company may modify all these details at any time*