



LUBRICANT WITH TEFLON SOROFLON

SOROFLON is a dry lubricant. It is used to reduce the effects of rubbing. By virtue of the remarkable properties of PTFE, which is clean, dry and non-oily, chemically inert, and capable of tolerating very various environmental conditions, **SOROFLON** is very valuable as a lubricant.

When it is applied to surfaces, PTFE endows them with an extremely low friction coefficient, and this provides excellent lubrication.

It can be applied to all materials - wood, plastic, metal, rubber, etc.

It is used on sliders, bridge panels, drawers, pulley axles, control bars, trolleys, turnbuckle, runners, sailcloth, bags, clothing, etc.

On surface subject to high speeds and high loads, **SOROFLON** can be removed from the surface by abrasion, and a new application is then required.

PHYSICAL CHARACTERISTICS

Main active element: PTFE (Polytetrafluoroethylene)

Appearance: Colourless liquid

Density: About 750 kg/dm³ at 20°C

Flash point: < 0°C

Self-igniting temperature:
Solubility: Not very mixable in water, soluble in solvent

APPLICATION

Shake the aerosol well before use, and purge afterwards.

Apply the spray at 20 - 30 cm from the clean, dry, grease-free surface to be lubricated. Leave to dry for a few moments.

PACKING AND STORAGE

PRECAUTIONS FOR USE

Container under pressure. Must be protected from direct sunlight. Do not expose to temperature over 50°C. Do not puncture the can, or burn it after use. Keep away from all sources of ignition. Do not smoke. Keep out of reach of children. Use only in a well ventilated area. Ventilate well after use. Do not breathe vapour.

HEALTH AND SAFETY

See data sheet

This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.

Our company may modify all these details at any time