



# PRODUCT FOR THE DE-OXIDATION OF ALUMINIUM

## DEROCH'ALU

**DEROCH'ALU** is a special product of acids, wetting agents and accelerators used for de-oxidation of light alloys. It is used for the de-oxidation of aluminium before painting, to brighten the surfaces of aluminium and stainless steel. This product is free of chromic acid, and acts rapidly as a result. It must not be used on magnesium-containing surfaces. In contact with lacquers, the product denatures the colour. In the case of contact with paint, wash copiously with water immediately.

The product has a strong de-greasing action.

---

### PHYSICAL CHARACTERISTICS

pH : ..... 1  
Appearance : ..... Colourless liquid fluid  
Density : ..... 1.17  
Solubility : ..... In all proportions  
Flash point : ..... > 60°C

#### Basic component

- Mineral acids
- Wetting agents

---

### APPLICATION

Application by brush or atomiser.  
Use the product at high concentration - 1 volume of product for 1 to 2 of water. Add the **DEROCH'ALU** to the water.  
Application is by atomising or by brushing onto the badly oxidised parts.  
Leave to act for 10 minutes, then rinse carefully with water.

---

### PACKING AND STORAGE

Packaging : ..... 1 litre, 5 litres and 30 litres  
Storage: ..... Pot life : 12 months  
Storage temperature : 0 to 35°C

---

### PRECAUTIONS FOR USE

If dilution, already put the product in water.

---

### HEALTH AND SAFETY

See data sheet

---

This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.  
Our company may modify all these details at any time