



## LUBRICANT FOR A MARINE ENVIRONMENT

# SOROSUIF

**SOROSUIF** is used for de-greasing and effective lubrication, even in the presence of water, and is employed a great deal on boats and in the navy.

Presentation of the product as an aerosol makes it practical and easy to use at once.

It is used for the lubrication of all parts working in a very damp atmosphere - turnbuckle, control bars, pulley axles, etc.

---

### PHYSICAL CHARACTERISTICS

Appearance : ..... Clear liquid  
Colour : ..... Colourless  
pH value : ..... -  
Flash point : ..... None  
Self-igniting temperature : ..... >200°C  
Aerosol pressure : ..... About 2.5 bars at 20°C  
Density : ..... 1114 kg/dm<sup>3</sup> at 20°C  
Solubility : ..... Soluble in alcohol and most common solvents, slightly soluble in water

---

### APPLICATION

Shake the aerosol well before use.

Warm the aerosol before use by holding it in the hand for a few minutes, if the temperature is low.

Spray at about 15 cm from the surface to be lubricated. Leave to dry.

Purge the aerosol after use in order to prevent blockage of the spray head.

---

### PACKING AND STORAGE

Packaging : ..... Aerosol of 200 ml

Storage: ..... Do not store in the cold.

Store in a well-ventilated place, away from sources of heat, frost, damp and ignition.

---

### PRECAUTIONS FOR USE

Container under pressure. Must be protected from direct sunlight. Do not expose to temperature over 50°C. Do not puncture the can, or burn it after use. Keep away from all sources of ignition. Do not smoke. Keep out of reach of children. Use only in a well ventilated area. Ventilate well after use. Do not breathe vapour.

---

### HEALTH AND SAFETY

See data sheet

---

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.*

*Our company may modify all these details at any time*