



HULL AND DECK RETOUCHING PAINT

Especially produced to make retouch on polyester gelcoat after sanding.

PHYSICAL CHARACTERISTICS

Aspect: Liquid
Flash point: < to 0°C (no propellant)
Solubility: No soluble
Density: More heavy that area

PREPARATION OF THE SURFACE

Carefully prepare the surfaces to be painted. The surface must be clean, dry and grease free

APPLICATION

Shake the aerosol (the ball inside must make a clear sound). In cold weather, to heat the aerosol with the bath Marie (30°C approximately).
First, spray onto a small surface. To pulverize of a regular movement and in layers crossed at a distance from 25 to 30 cm of surface to paint.

PACKING AND STORAGE

Packaging : Aerosol 150 ml
Storage : Between 5 to 40°C

PRECAUTIONS FOR USE

Pressurised container. Protect from sunlight. Do not expose to temperatures higher than 50 degrees. Do not puncture or burn even after use.
Do not spray towards a flame or an incandescent substance. Do not breathe vapours. Avoid the contact with eyes and skin. Do not smoke. Do not eat and drink when using.
Keep out of reach of children.

HEALTH AND SAFETY

See data sheet

*This information corresponds to the actual state of our knowledge and has the sole object of informing you about our products and possible applications. It is objectively given but does not imply any guarantee by us.
Our company may modify all these details at any time*