

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A**



**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : COLLE EPOXY TOPFIX - COMPOSANT A

Product code : RP070020A.

UFI : 3300-F0GU-P005-AMSV

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

N/A

**1.3. Details of the supplier of the safety data sheet**

Registered company name : SOROMAP PEINTURES VERNIS.

Address : RUE MAURICE MALLET Z.A. DE BELIGON.17300.ROCHEFORT SUR MER.FRANCE.

Telephone : 05.46.88.36.10. Fax : 05.46.88.36.15.

contact@soromap.com

www.soromap.com

**1.4. Emergency telephone number : +33 (0)1 45 42 59 59.**

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Skin irritation, Category 2 (Skin Irrit. 2, H315).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Skin sensitisation, Category 1 (Skin Sens. 1, H317).

Hazardous to the aquatic environment - Chronic hazard, Category 2 (Aquatic Chronic 2, H411).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

**2.2. Label elements**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS09



GHS07

Signal Word :

WARNING

Product identifiers :

EC 216-823-5

CAS 9003-36-5

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE

EPICHLOROHYDRIN-FORMALDEHYDE-PHENOL POLYMER NUMBER AVERAGE MOLECULAR WEIGHT <+ 700

Additional labeling :

EUH205

Contains epoxy constituents. May produce an allergic reaction.

Hazard statements :

H315

Causes skin irritation.

## COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statements - Prevention :	
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures****Composition :**

Identification	Classification (EC) 1272/2008	Note	%
CAS: 1675-54-3 EC: 216-823-5 REACH: 01-2119456619-26 BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 2, H411		50 $\leq$ x % < 100
CAS: 9003-36-5 REACH: 01-2119454392-40 EPICHLOROHYDRIN-FORMALDEHYDE-PHENOL POLYMER NUMBER AVERAGE MOLECULAR WEIGHT $\leq$ 700	GHS07, GHS09 Wng Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		2.5 $\leq$ x % < 10
CAS: 2530-83-8 EC: 219-784-2 REACH: 01-2119513212-58 TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE	GHS05 Dgr Eye Dam. 1, H318 Aquatic Chronic 3, H412		1 $\leq$ x % < 2.5

**Specific concentration limits:**

Identification	Specific concentration limits	ATE
CAS: 1675-54-3 EC: 216-823-5 REACH: 01-2119456619-26 BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE	Skin Irrit. 2: H315 $\geq 5\%$ Eye Irrit. 2: H319 $\geq 5\%$	
CAS: 2530-83-8 EC: 219-784-2 REACH: 01-2119513212-58 TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE		dermal: ATE = 4250 mg/kg BW

**Information on ingredients :**

(Full text of H-phrases: see section 16)

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A**

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

No data available.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A****6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid skin and eye contact with this mixture.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters**

No data available.

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

**Final use:**

Exposure method:

Potential health effects:

DNEL :

**Workers.**

Dermal contact.

Short term systemic effects.

21 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Dermal contact.

Long term systemic effects.

21 mg/kg body weight/day

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Short term systemic effects.

147 mg of substance/m3

Exposure method:

Potential health effects:

DNEL :

Inhalation.

Long term systemic effects.

147 mg of substance/m3

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

**Final use:**

Exposure method:

Potential health effects:

**Workers.**

Dermal contact.

Long term systemic effects.

## COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A

DNEL : 8.33 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Short term systemic effects.  
DNEL : 8.33 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term local effects.  
DNEL : 12.25 mg of substance/m3

Exposure method: Inhalation.  
Potential health effects: Short term systemic effects.  
DNEL : 12.25 mg of substance/m3

**Final use:****Consumers.**

Exposure method: Ingestion.  
Potential health effects: Short term systemic effects.  
DNEL : 0.75 mg/kg body weight/day

Exposure method: Ingestion.  
Potential health effects: Long term systemic effects.  
DNEL : 0.75 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Short term systemic effects.  
DNEL : 3.571 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term systemic effects.  
DNEL : 3.571 mg/kg body weight/day

**Predicted no effect concentration (PNEC):****TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)**

Environmental compartment: Soil.  
PNEC : 0.13 mg/kg

Environmental compartment: Fresh water.  
PNEC : 1 mg/l

Environmental compartment: Sea water.  
PNEC : 0.1 mg/l

Environmental compartment: Intermittent waste water.  
PNEC : 1 mg/l

Environmental compartment: Fresh water sediment.  
PNEC : 0.79 mg/kg

Environmental compartment: Waste water treatment plant.  
PNEC : 10

**BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)**

Environmental compartment: Soil.  
PNEC : 0.196 mg/kg

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A**

Environmental compartment: PNEC :	Fresh water. 0.006 mg/l
Environmental compartment: PNEC :	Sea water. 0.0006 mg/l
Environmental compartment: PNEC :	Intermittent waste water. 0.018 mg/l
Environmental compartment: PNEC :	Fresh water sediment. 0.996 mg/kg
Environmental compartment: PNEC :	Marine sediment. 0.0996 mg/kg
Environmental compartment: PNEC :	Waste water treatment plant. 10 mg/l

**8.2. Exposure controls****Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

## COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

## 9.1. Information on basic physical and chemical properties

**Physical state**

Physical state : Viscous liquid.

**Odour**

Odour threshold : Not stated.

**Melting point**

Melting point/melting range : Not specified.

**Freezing point**

Freezing point / Freezing range : Not stated.

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : Not specified.

**Flammability**

Flammability (solid, gas) : Not stated.

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

**Flash point**

Flash Point : 150.00 °C.

**Auto-ignition temperature**

Self-ignition temperature : Not specified.

**Decomposition temperature**

Decomposition point/decomposition range : Not specified.

**pH**

pH : Not relevant.

pH (aqueous solution) : Not stated.

**Kinematic viscosity**

Viscosity : 8.000-12.000 mPa.s

**Solubility**

Water solubility : Insoluble.

Fat solubility : Not stated.

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Not relevant.

**Density and/or relative density**

Density : 1.15 à 25°C

**Relative vapour density**

Vapour density : Not stated.

**Particle characteristics**

The mixture does not contain nanoforms.

## 9.2. Other information

VOC (g/l) : 0.00

## 9.2.1. Information with regard to physical hazard classes

No data available.

## 9.2.2. Other safety characteristics

No data available.

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A****SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Avoid :

- humidity

**10.5. Incompatible materials**

Keep away from :

- water

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

May cause an allergic reaction by skin contact.

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and a respiratory tract sensitiser as well as an irritant.

Constituents with a low molecular weight irritate the eyes, mucous membranes and the skin

Repeated contact with the skin may cause irritation and hypersensitisation, possibly in combination with other epoxide compounds.

**11.1.1. Substances****Acute toxicity :**

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

Dermal route :

LD50 = 4250 mg/kg bodyweight/day

Species : Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Dusts/mist) :

LC50 > 5.3 mg/l

OECD Guideline 403 (Acute Inhalation Toxicity)

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

Oral route :

LD50 > 2000 mg/kg bodyweight/day

Species : Rat

OECD Guideline 420 (Acute Oral Toxicity Fixed Dose Method)

Dermal route :

LD50 > 2000 mg/kg bodyweight/day

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

**Skin corrosion/skin irritation :**

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

Species : Rabbit



**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A**

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

Effect observed : Overall irritation score

Species : Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Respiratory or skin sensitisation :**

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

Buchler Test :

Non-sensitiser.

Species : Others

OECD Guideline 406 (Skin Sensitisation)

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

May cause an allergic skin reaction.

Local lymph node stimulation test :

Sensitiser.

Species : Mouse

OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**11.1.2. Mixture****Respiratory or skin sensitisation :**

Contains epoxy compounds. May cause an allergic reaction.

**11.2. Information on other hazards****Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 1675-54-3 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

**SECTION 12 : ECOLOGICAL INFORMATION**

Toxic to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

**12.1. Toxicity****12.1.1. Substances**

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

Crustacean toxicity :

EC50 = 1.7 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 0.3 mg/l

Species : Daphnia magna

Duration of exposure : 21 days

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

Fish toxicity :

LC50 = 55 mg/l

Species : Cyprinus carpio

Duration of exposure : 96 h

Crustacean toxicity :

NOEC &gt; 100 mg/l

Species : Daphnia magna

Duration of exposure : 21 days

OECD Guideline 211 (Daphnia magna Reproduction Test)

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A****12.2. Persistence and degradability****12.2.1. Substances**

TRIMETHOXY[3-(OXIRAN-2-YLMETHOXY)PROPYL]SILANE (CAS: 2530-83-8)

Biodegradability : Non-rapidly degradable.

EPICHLOROHYDRIN-FORMALDEHYDE-PHENOL POLYMER NUMBER AVERAGE MOLECULAR WEIGHT <+ 700  
(CAS: 9003-36-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

Biodegradability : Non-rapidly degradable.

**12.3. Bioaccumulative potential****12.3.1. Substances**

BIS[4-(2,3-EPOXYPROPOXY)PHENYL]PROPANE (CAS: 1675-54-3)

Octanol/water partition coefficient : log K<sub>ow</sub> = 3.242  
OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

No data available.

**12.7. Other adverse effects**

No data available.

**German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :**

WGK 2 : Hazardous for water.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2023 - IMDG 2022 [41-22] - ICAO/IATA 2023 [64]).

**14.1. UN number or ID number**

3082

**14.2. UN proper shipping name**

UN3082=ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(bis[4-(2,3-epoxypropoxy)phenyl]propane)

## COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A

## 14.3. Transport hazard class(es)

- Classification :



9

## 14.4. Packing group

III

## 14.5. Environmental hazards

- Environmentally hazardous material :



## 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	9	M6	III	9	90	5 L	274 335 375 601	E1	3	-

Not subject to this regulation if Q &lt;= 5 l / 5 kg (ADR 3.3.1 - DS 375)

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	9	-	III	5 L	F-A. S-F	274 335 969	E1	Category A	-

Not subject to this regulation if Q &lt;= 5 l / 5 kg (IMDG 3.3.1 - 2.10.2.7)

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	9	-	III	964	450 L	964	450 L	A97 A158 A197 A215	E1
	9	-	III	Y964	30 kg G	-	-	A97 A158 A197 A215	E1

Not subject to this regulation if Q &lt;= 5 l / 5 kg (IATA 4.4.4 - DS A197)

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

Marine pollutant (IMDG 3.1.2.9):(bis[4-(2,3-epoxypropoxy)phenyl]propane)

## 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

## Container information:

The mixture is contained in packaging that does not exceed 125 ml.

## Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

## Explosives precursors :

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

## Particular provisions :

No data available.

**COLLE EPOXY TOPFIX - COMPOSANT A - RP070020A****German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :**

WGK 2 : Hazardous for water.

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Abbreviations and acronyms :**

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS07 : Exclamation mark

GHS09 : Environment

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.